

南开大学  
Nankai University

MBA中心

# Modern Logistics & Supply Chain Management

## ML & SCM

Queueing Theory  
Part I - Introduction

*As gold which he cannot spend  
will make no man rich,  
so knowledge which he cannot apply  
will make no man wise.*  
Samuel Johnson: The Idler No. 84

*I'm British. I know how to queue.*  
Douglas Adams, The Hitchhiker's Guide to the Galaxy

Dr. Wolfgang Garn  
Winter, 2016

---

---

---

---

---

---

---

---

南开大学  
Nankai University

MBA中心

# Learning Objectives

- To know waiting line principles
- To derive operating characteristics
- To know Little's Law
- To be familiar with the Single-Server Waiting Line System

Winter 2016 ML&SCM 2

---

---

---

---

---

---

---

---

南开大学  
Nankai University

MBA中心

# A Single-Server Waiting Line System

Figure 13.1

---

---

---

---

---

---

---

---

Overview

南開大學  
Nankai University

MBAS中心

- Significant amount of **time spent** in waiting lines by people, products, etc.
- Providing **quick service** is an important aspect of **quality** customer service.
- The basis of waiting line analysis is the **trade-off** between the **cost of improving service** and the costs associated with making customers **wait**.
- Queuing analysis is a **probabilistic** form of analysis.
- The results are referred to as **operating characteristics**.
- Results are used by *managers* of queuing operations to make **decisions**.

Winter 2016

MLAS/SCM

4

---

---

---

---

---

---

---

Queueing System

南開大學  
Nankai University

MBAS中心

- Waiting Line System = Queueing System

The diagram illustrates a queueing system. It starts with a 'source' where 'customers arriving' enter a 'queue' where 'customers waiting' are represented by green rectangles. From the queue, 'customers serviced' move to a 'server' (green circle). Finally, 'customers departing' leave the system at a 'sink'. An inset image shows a 3D model of a retail store layout with people in a queue.

Entity ~ atom ~ element ~ item ~ customer

Winter 2016

MLAS/SCM

5

---

---

---

---

---

---

---

Queueing time events

南開大學  
Nankai University

MBAS中心

The diagram shows a timeline for a customer's experience. The 'Customer' timeline includes arrival time  $t_{a+1}$ , waiting time  $w_{n+1}$ , and service time  $s_{n+1}$ . The 'Queue' timeline shows the sequence of events: arrival, waiting, and service. The 'Server' timeline shows the sequence of events: service, gap, and departure. Key time points include  $t_{a+1}$ ,  $t_{s+1}$ ,  $t_{d+1}$ , and  $t_{a+2}$ . The diagram also shows the sequence of events for the next customer, starting with arrival time  $t_{a+2}$ .

Winter 2016

MLAS/SCM

6

---

---

---

---

---

---

---

Elements of  
Waiting Line Analysis

南開大學  
Nankai University

MBA中心

- Waiting lines form because **people or things arrive at a service faster** than they can be served.
- Most **operations have sufficient server capacity** to handle customers in the long run.
- Customers however, **do not arrive at a constant rate** nor are they served in an equal amount of time.

Winter 2016

MLASCM

7

---

---

---

---

---

---

---

Waiting Line Analysis  
Stable queueing systems

南開大學  
Nankai University

MBA中心

- Waiting lines are continually increasing and decreasing in length and **approach an average rate** of customer arrivals and an average service time, **in the long run**.

Stable Queueing System

$\gamma(t) = \int (\alpha(t) - \delta(t)) dt$

$\alpha(t)$  arrival

$\delta(t)$  departure

M/M/1  
 $E(t)=3, E(x)=4 \Rightarrow \rho=0.75$

Winter 2016

MLASCM

8

---

---

---

---

---

---

---

Instable Queueing System

南開大學  
Nankai University

MBA中心

Instable Queueing System

$\gamma(t) = \int (\alpha(t) - \delta(t)) dt$

$\alpha(t)$  arrival

$\delta(t)$  departure

M/M/1  
 $E(t)=4, E(x)=3 \Rightarrow \rho=1.33$

Utilisation ...  
is more than 100%  
More customers arrive ...  
than can be serviced

Winter 2016

MLASCM

9

---

---

---

---

---

---

---

### The Single-Server Waiting Line System

#### Summary

南开大学

Nankai University

MBA中心

- Components of a waiting line system include **arrivals** (customers), **servers**, (cash register/operator), customers in line form a **waiting line**.
- Factors to consider in analysis:
  - queue discipline
  - arrival rate
  - service rate

Winter 2016

ML&SCM

10

---

---

---

---

---

---

---

### Elements of Waiting Line Analysis

南开大学

Nankai University

MBA中心

- **Decisions** concerning the management of waiting lines are **based on these averages** for customer arrivals and service times.
- They are used in formulas to compute operating characteristics of the system which in turn form the basis of decision making.

Winter 2016

ML&SCM

11

---

---

---

---

---

---

---

### Single-Server Waiting Line System

#### Component Definitions

南开大学

Nankai University

MBA中心

- **Queue Discipline:** The order in which waiting customers are served.
- **Calling Population:** The source of customers (infinite or finite).
- **Arrival Rate:** The frequency at which customers arrive at a waiting line according to a probability distribution (frequently described by a Poisson distribution).
- **Service Rate:** The average number of customers that can be served during a time period (often described by the negative exponential distribution).

Winter 2016

ML&SCM

12

---

---

---

---

---

---


---

Dr. Wolfgang Garn

4

### Kendall Notation

- A/B/s/C/P/D
  - Arrival Distribution (A)
  - Departure Distribution (B)
  - Number of servers (s)
  - System capacity (C)
  - Population size (P)
  - Queueing discipline (D)
- Example: M/M/1
  - Arrival and service follows an exponential distribution
  - Single server
  - “Implicit: “ infinite capacity & population, FCFS



Nankai University

MBA中心

Winter 2016

ML&SCM

13

---

---

---

---

---


---

---

---

### Typical Arrival and Departure Distributions

- G ... General Distribution (any)
- M ... Exponential Distribution (i.e. Markovian)
- E ... Erlang Distribution
- D ... Deterministic Distribution
- H ... Hyper-Exponential Distribution



Nankai University

MBA中心

Winter 2016

ML&SCM

14

---

---

---

---

---

---


---

---

### Single-Server Waiting Line System

#### Single-Server Model

- Assumptions of the basic single-server model:
  - An infinite calling population
  - A first-come, first-served queue discipline
  - Poisson arrival rate
  - Exponential service times
- Symbols:
  - $\lambda$  = the arrival rate (average number of arrivals/time period)
  - $\mu$  = the service rate (average number served/time period)
- Customers must be served faster than they arrive ( $\lambda < \mu$ ) or an infinitely large queue will build up.



Nankai University

MBA中心

Winter 2016

ML&SCM

15

---

---

---

---

---


---

---

---

Time & Rate

- Expected interarrival time  $E(t)$ 
  - Arrival rate  $\lambda$ 
$$\lambda = \frac{1}{E(t)}$$
- Expected service time
  - Service rate  $\mu$ 
$$\mu = \frac{1}{E(x)}$$



Winter 2016

ML&SCM

16

---

---

---

---

---


---

---

---

Single Server System

- Arrival rate:  $\lambda$ 
  - e.g. 3 customers arrive per hour (in the queue)
- Service rate:  $\mu$ 
  - e.g. 4 customers can be serviced per hour
- Utilisation:  $U$  or  $\rho$ 
  - e.g.  $\frac{3}{4} = 75\%$



Winter 2016

ML&SCM

17

---

---

---

---

---

---

---


---

Birth-Death process

- State 0: No customer in system
  - Probability of being in  $p_0$ 

An intellectual challenge


$$\lambda p_0 = \mu p_1 \Rightarrow p_1 = \frac{\lambda}{\mu} p_0$$



- State 1: one customer in system
$$\lambda p_0 + \mu p_2 = \lambda p_1 + \mu p_1 \Rightarrow p_2 = \frac{\lambda^2}{\mu^2} p_0 \Rightarrow p_k = \frac{\lambda^k}{\mu^k} p_0$$

Winter 2016

ML&SCM

 The Greek Alphabet

18

---

---

---

---

---

---

---

---

南開大學  
Nankai University

MBA中心


Probabilities

- Probability of  $k$  customers
- Probability of “all” customers
- Probability of no customer in the system

$$p_k = \frac{\lambda^k}{\mu^k} p_0 = \rho^k p_0$$
$$\sum_{k=0}^{\infty} \rho^k p_0 = 1$$
$$1 = \sum_{k=0}^{\infty} \rho^k p_0 = p_0 \sum_{k=0}^{\infty} \rho^k \Rightarrow p_0 = \frac{1}{\sum_{k=0}^{\infty} \rho^k} = 1 - \rho$$

$$s = 1 + \rho + \rho^2 + \rho^3 + \dots$$
$$-s\rho = -\rho - \rho^2 - \rho^3 - \dots$$
$$s - s\rho = 1 \Rightarrow s = \frac{1}{1 - \rho}$$

Geometric series



Winter 2016

MBA/SCM

20

---

---

---

---

---

---

---


---


南開大學  
Nankai University

MBA中心

Customers in System  
M/M/1

- Average number of customers in system


$$p_0 = 1 - \rho \quad \rho = \frac{\lambda}{\mu}$$
$$p_k = (1 - \rho)\rho^k$$
$$L = \sum_{k=0}^{\infty} k p_k = \sum_{k=0}^{\infty} k (1 - \rho) \rho^k = (1 - \rho) \rho \sum_{k=1}^{\infty} k \rho^{k-1} = (1 - \rho) \rho \frac{d}{d\rho} \sum_{k=0}^{\infty} \rho^k$$
$$= (1 - \rho) \rho \frac{1}{(1 - \rho)^2} = \frac{\rho}{(1 - \rho)}$$
$$L = \frac{\rho}{(1 - \rho)} = \frac{\frac{\lambda}{\mu}}{(1 - \frac{\lambda}{\mu})} = \frac{\lambda}{\mu - \lambda}$$



A.K. Erlang

$$\frac{d}{d\rho} \rho^k = k \rho^{k-1}$$
$$\frac{d}{d\rho} \frac{1}{1 - \rho} = \frac{1}{(1 - \rho)^2}$$

Winter 2016

MBA/SCM

21

---

---

---

---

---

---

---

---

南開大學  
Nankai University

MBA中心


Little's Law

- “relates numbers and times”

What could the relation be?

- Arrival rate = ~~mean system time~~ x ~~mean number of customers~~
- Mean number of customers in the system = arrival rate x mean system time
- ~~mean system time~~ = ~~mean number of customers~~ x ~~arrival rate~~

Proven by  
John Little in  
1961



John at Euro 2016 –  
INFORMS conference,  
Italy

Winter 2016

MBA/SCM

21

---

---

---

---

---

---

---

---

Little's Law

- $L = \lambda W$
- #customers = arrival rate x system time
- And it even holds for
  - the queue and server, i.e.
    - $L_q = \lambda W_q$
    - $L_s = \lambda W_s$
- Why?
  - The number of customers entering the system is equal to those completing the service.
  - No customers/jobs are created or lost within the system.
- Note this formula applies for all waiting line systems

Winter 2016

ML&SCM

22

---

---

---

---

---

---

---

---

System characteristics

M/M/1

- Average number of customers in system:
  - $L = \frac{\rho}{(1-\rho)} = \frac{\lambda}{\mu-\lambda}$
- Average time a customer spends in the system:
  - Little's law:  $L = \lambda W$  implies  $W = \frac{L}{\lambda}$
  - $W = \frac{1}{\mu-\lambda}$

Winter 2016

ML&SCM

23

---

---

---

---

---

---

---

---

Server and Queue characteristics

M/M/1

- Server
  - service rate  $\mu$  is known  $\Rightarrow$
  - Avg. service time  $W_s = \frac{1}{\mu}$ 
    - via Little's Law  $\Rightarrow$
  - Avg. #customers  $L_s = \frac{\lambda}{\mu}$  in service
- Queue
  - we know  $W$  and  $W_s \Rightarrow$

$W = \frac{1}{\mu-\lambda}$

$W_q = \frac{\lambda}{(\mu-\lambda)\mu}$

$L_q = \frac{1}{(\mu-\lambda)\mu}$

Winter 2016

ML&SCM

24

---

---

---

---

---

---

---

---



Single-Server Waiting Line System

Operating Characteristics: Fast Shop Market (1 of 3)

南开大学  
Nankai University

MBA中心

- $\lambda = 24$  customers per hour arrive at checkout counter
- $\mu = 30$  customers per hour can be checked out
- What is the utilisation?
  - $\rho = \frac{\lambda}{\mu} = \frac{24}{30} = 80\%$
- Is the system stable?
  - Yes, because  $\rho < 100\%$
- What is the probability that the system idle?
  - $1 - \rho = 20\%$
- What is the probability that no customer is in the system?
  - $p_0 = 1 - \rho = 20\%$

Winter 2016

ML&SCM

25

---

---

---

---

---

---

---

---

Single-Server Waiting Line System

Operating Characteristics: Fast Shop Market (2 of 3)

南开大学  
Nankai University

MBA中心

- How many customers are in the shop?
  - $L = \frac{\lambda}{\mu - \lambda} = \frac{24}{30 - 24} = 4$  customers on average
- How much time do they spend there?
  - $W = \frac{L}{\lambda} = \frac{4}{24} = \frac{1}{6}$  of an hour, i.e. 10 minutes on average
- How fast is the service?
  - $W_s = \frac{1}{\mu} = \frac{1}{30}$  of an hour, i.e.  $\frac{60}{30} = 2$  minutes

Winter 2016

ML&SCM

26

---

---

---

---

---

---

---

---

Single-Server Waiting Line System

Operating Characteristics: Fast Shop Market (3 of 3)

南开大学  
Nankai University

MBA中心

- How many customers are in service?
  - $L_s = \frac{\lambda}{\mu} = \frac{24}{30} = 0.8$  customers on average
- How long to they have to wait?
  - $W_q = W - W_s = 10 - 2 = 8$  minutes on average
- How many people are waiting?
  - $L_q = \lambda W_q = 24 \cdot \frac{8}{60} = L - L_s = 4 - 0.8 = 3.2$  customers on average

Winter 2016

ML&SCM

27

---

---

---

---

---

---

---

---

UNIVERSITY OF  
TIANJIN

南开大学  
Nankai University

MBAS中心

Recap

- What are three main components in waiting lines?
  - queue, service, system
- What are operating characteristics?
  - Number of entities in queue, service and system
  - Time in queue, service and system
- What's the purpose of Little's Law?
  - "To link time and entity numbers"

Winter 2016

ML&SCM

28

---

---

---

---

---

---

---

---


UNIVERSITY OF  
TIANJIN

南开大学  
Nankai University

MBAS中心

The End

- Any questions?



Winter 2016

ML&SCM

29

---

---

---

---

---

---

---

---